



360 FREIGHT SOLUTIONS

360 Freight Solutions Pte Ltd

5 Ang Mo Kio Industrial Park 2 A , # 07-28 AMK Tech II Singapore 567760

Tel: +65.9327 4293 | Fax: +65 6286 3146

Email : william@360FS.com.sg

UEN: 201505172H


Container Specification

20GP/40GP/HQ



They are suitable for most types of cargo.

20/40 Platform Container



Platform containers are without sides, ends and roof.

They are used for odd-sized cargo which does not fit on or in any other type of container.

20/40 RF (Reefer)




Reefer containers or refrigerated containers are used to transport goods requiring temperature-controlled conditions in transit, such as fruit, vegetables, dairy products and meat.

Open Top Container



Open top containers have an open top covered by a tarpaulin instead of a solid roof. This enables oversized cargo such as timber and scrap metal to be loaded from the top.

Flat Rack Containers



Flat Rack are especially suitable for heavy loads and cargo that needs loading from the top or sides, such as pipes and machinery. You will find collapsible containers and non-collapsible containers with or without walls.

	Internal Dimension	Door Opening	Empty Contr Weight	Maximum Cargo Weight	Gross Capacity	Maximum Capacity
20 GP	L: 5.896 m W: 2.35 m H: 2.385 m	W: 2.34 m H: 2.274 m	2,150.0 Kg	24,850.0 Kg	33.0 m3	28.0 m3
40 GP	L: 12.035 m W: 2.35 m H: 2.393 m	W: 2.339 m H: 2.274 m	3,700.0 Kg	28,800.0 Kg	67.0 m3	56-58.0 m3
40 HQ	L: 12.035 m W: 2.35 m H: 2.697 m	W: 2.339 m H: 2.577 m	3,800.0 Kg	30,200.0 Kg	76.0 m3	62-65.0 m3
20 RF (Reefer)	L: 5.430 m W: 2.286 m H: 2.155 m	W: 2.286 m H: 2.188 m	2,750.0 Kg	24,250.0 Kg	26.8 m3	22-25.0 m3
40 RF (Reefer)	L: 11.577 m W: 2.294 m H: 2.110 m	W: 2.294 m H: 2.174 m	3,900.0 Kg	28,600.0 Kg	56.1 m3	48-53.0 m3
20 OT (Open Top)	L: 5.893 m W: 2.346 m H: 2.353 m	W: 2.338 m H: 2.273 m	2,250.0 Kg	28,230.0 Kg	32.0 m3	25-27.0 m3
40 OT (Open Top)	L: 12.043 m W: 2.338 m H: 2.272 m	W: 2.289 m H: 2.253 m	4,300.0 Kg	26,180.0 Kg	64.0 m3	53-55.0 m3
20 FT (Flat Rack)	L: 5.935 m W: 2.398 m H: 2.327 m		2,560.0 Kg	21,440.0 Kg		
40 FT (Flat Rack)	L: 12.010 m W: 2.228 m H: 1.981 m		4,200.0 Kg	40,800.0 Kg		
20 PF (Platform)	L: 6.06 m W: 2.44 m		2,740.0 Kg	31,260.0 Kg		
40 PF (Platform)	L: 12.19 m W: 2.44 m		5,700.0 Kg	39,300.0 Kg		

IMPORTANT: The specifications given are an indication only. Variations can be found between series and makes.